



TM

**AEROFLON ENGINEERS PVT. LTD.**

B-505, Premium House, 5th Floor, Opp. Gandhigram Railway Station, Ahmedabad - 380 009. Gujarat. India.

Ph.: +91 79 26589712 Fax: +91 79 26586954 M: +91 9824049737

Email: info@aeroflon.com W: <http://www.aeroflon.com> Official Blog: <http://blog.aeroflon.com>

## H PLUS LUBRICANT FOR SCREW AIR COMPRESSOR PREMIUM LUBRICANT

### Applications:

The H PLUS is a high performance, multifunctional compressor and vacuum pump lubricant designed for use by those that need a step up in performance from the typical petroleum oil. These may be considered environmentally friendly since they are zinc free. These premium oils are designed to give improved performance. The H PLUS has a service life of 8,000 – 24,000 hours under good operating conditions in Centrifugal Compressors.

### **Typical Industrial Applications:**

- Rotary Screw Compressors
- Rotary Vane Compressors
- Centrifugal Compressors
- Reciprocating Compressors
- Vacuum Pumps
- High Pressure Hydraulic Systems
- High Pressure Turbines

### Performance Benefits:

- Excellent rust and oxidation inhibitors
- Zinc free
- Will not foam
- Great demulsibility

Typical Properties	Test Method	H PLUS
ISO Grade	ASTM D2422	32
Viscosity @ 40 Deg C	ASTM D445	32
Viscosity @ 100 Deg C	ASTM D445	5.6
Viscosity Index	ASTM D2270	113
Flash Point Deg C/F	ASTM D92	206 / 402
Pour Point Deg C/F	ASTM D97	-34 / -29
Copper Corrosion	ASTM D130	1a
Foaming Sequences I, II, III	ASTM D892	Pass
Specific Gravity	ASTM D1298	0.87

**MADE IN USA**