



TM

**AEROFLOX ENGINEERS PVT. LTD.**

B-505, Premium House, 5th Floor, Opp. Gandhigram Railway Station, Ahmedabad - 380 009. Gujarat. India.

Ph.: +91 79 26589712 Fax: +91 79 26586954 M: +91 9824049737

Email: info@aeroflon.com W: http://www.aeroflon.com Official Blog: http://blog.aeroflon.com

## **X-Tend COMPRESSOR OIL**

### 100% SYNTHETIC COMPRESSOR LUBRICANT

**Applications:**

The X-Tend Compressor Oil is fully synthetic compressor oil that is formulated with the highest quality poly alpha olefin (PAO) base fluids. These 100% premium synthetic oils are used where maximum seal, paint, and plastic compatibility is required. These are designed for rotary screw applications and offer a service life of 8,000 – 9000 hours under a wide range of temperatures under good operating conditions.

**Typical Industrial Applications:**

- Rotary Screw Compressors
- Rotary Vane Compressors
- Centrifugal Compressors
- Vacuum Pumps

**Performance Benefits:**

- Outstanding thermal oxidative stability
- Very low pour point
- Wide operating temperature range
- Non-detergent and ash less
- Extended drain intervals / reduced oil disposal
- Excellent vapor pressure characteristics
- USDA H-2 authorized

<b>TYPICAL PROPERTIES</b>	<b>TEST METHOD</b>	<b>X-Tend</b>
ISO Grade	ASTM D2422	46
Viscosity @ 40 Deg Celsius	ASTM D445	48
Viscosity @ 100 Deg Celsius	ASTM D445	7.9
Viscosity Index	ASTM D2270	134
Flash Point, C/F	ASTM D92	251 / 483
Pour Point, C/F	ASTM D97	-51 / -60
Copper Corrosion	ASTM D130	1b, shiny
Foaming Sequences I, II, III	ASTM D892	Nil
Demulsibility	ASTM D1401	40-40-0 (10)
Four Ball Wear, 40 Kg., 1200 RPM, 75 Deg Celsius, 1 Hr., Scar Diameter, mm	ASTM D4172	0.43
Specific Gravity	ASTM D1298	0.86

**MADE IN USA**